

Technical data

Designation	Description
TLGB 20	SKF Battery driven grease gun (with 220-240V charger)
TLGB 20/110V	SKF Battery driven grease gun (with 110V charger)
Voltage charger, V/Hz	
TLGB 20	200-240 V/50-60Hz
TLGB 20/110V	110-120 V/60Hz
Maximum operating pressure	400 bar (6 000 psi)
Maximum peak pressure	700 bar (10 000 psi)
Grease nozzle	4 jaws (suitable for nipples according to DIN 71412)
Operating temperature range*	-20 to +50 C (0 to 120 F)*
Grease NLGI2	Up to 2
Grease output	
Low speed setting	100 ml/min. (3.5 oz/min) at 70 bar pressure
High speed setting	160 ml/min (5.5 oz/min) at 70 bar pressure
Length of hose	900 mm (36 in)
Charge time battery	1.5 hours
Battery type	Li-ion
Battery output	20 V DC maximum (without workload)
Battery capacity	1500 mAh
Weight/dimensions:	
Weight of grease gun (including battery)	3,0 kg (6,5 lbs)
Dimensions of carrying case (W x D x H)	590 mm x 110 mm x 370 mm
Total weight (including case)	5.7 kg (12,7 lbs)

* Grease meter accuracy compromised below 0°C

Accessories

Designation	Description
TLGB 20-1	Carrying strap for battery driven grease gun
TLGB 20-2	20V Li-Ion battery for battery driven grease gun

Replacement parts

Designation	Description
TLGB 20-3	High pressure hose 900 mm (36in) with coupler for battery driven grease gun
TLGB 20-4	Grease tube assembly for battery driven grease gun
TLGB 20-5	Charger 220-240V for battery driven grease gun
TLGB 20-6	Charger 110V for battery driven grease gun