



Shut-off valves with male thread and plug connection

»blue series«

EASY

Shut-off valve with male thread and plug connection, flow direction from port to tube, conical male thread, coated

Art. No.	Type No.	L1 mm	L2 mm	a/f mm
110091	192.014-12	72.3	47.0	21
110092	192.038-8	62.4	42.6	17
110093	192.038-10	73.4	47.0	17
110094	192.038-12	74.3	47.0	21
110095	192.012-10	76.9	47.0	21
110096	192.012-12	77.3	47.0	21



Shut-off valves with plug connection

»blue series«

EASY

Shut-off valve with plug connection

Art. No.	Type No.	L1 mm	L2 mm
110097	190.006	50.8	42.2
110098	190.008	51.8	42.3
110099	190.010	63.3	46.7
110100	190.012	64.1	46.8



190.006


3/2-way pilot valves with male thread

»blue series«

EASY

3/2-way pilot valve with parallel male thread with O-ring (NBR)

Art. No.	Type No.	Thread 1	Thread 2	L1 mm	L2 mm
110101	275.018	G 1/8	G 1/8	65.0	41.5
135946	275.1418	G 1/4	G 1/8	66.5	42.6
110102	275.014	G 1/4	G 1/4	68.0	41.5
135947	275.3814	G 3/8	G 1/4	80.0	47.0
110103	275.038	G 3/8	G 3/8	81.5	46.0
135948	275.1238	G 1/2	G 3/8	83.2	47.0
135949	275.012	G 1/2	G 1/2	86.7	47.0



275.014



3/2-way pilot valve with conical male thread, coated

Art. No.	Type No.	Thread 1	Thread 2	L1 mm	L2 mm
110104	276.018	R 1/8	R 1/8	65.0	41.5
135953	276.1418	R 1/4	R 1/8	66.5	42.6
110105	276.014	R 1/4	R 1/4	70.0	41.5
135954	276.3814	R 3/8	R 1/4	82.5	47.0
110106	276.038	R 3/8	R 3/8	83.5	46.0
135955	276.1238	R 1/2	R 3/8	87.5	47.0



276.014