


## Shut-off valves with male thread

»blue series«

EASY



### Shut-off valve, double parallel thread with O-ring (NBR)

Art. No.	Type No.	Thread 1	Thread 2	L1 mm	L2 mm	a/f mm
110061	194.1818	G 1/8	G 1/8	64.5	42.6	14/14
110062	194.1418	G 1/4	G 1/8	67.6	42.6	17/14
110063	194.1414	G 1/4	G 1/4	67.6	42.6	17/17
110064	194.3814	G 3/8	G 1/4	81.1	47.0	20/20
110065	194.3838	G 3/8	G 3/8	82.4	47.0	20/20
110066	194.1238	G 1/2	G 3/8	86.2	47.0	24/21
110067	194.1212	G 1/2	G 1/2	89.0	47.0	24/24

### Shut-off valve, double conical thread, coated

Art. No.	Type No.	Thread 1	Thread 2	L1 mm	L2 mm	a/f mm
110068	191.1818	R 1/8	R 1/8	65.0	42.6	12/12
110069	191.1418	R 1/4	R 1/8	67.5	42.6	14/12
110070	191.1414	R 1/4	R 1/4	70.0	42.6	14/14
110071	191.3814	R 3/8	R 1/4	82.0	47.0	17/14
110072	191.3838	R 3/8	R 3/8	83.5	47.0	17/17
110073	191.1238	R 1/2	R 3/8	87.0	47.0	21/17
110074	191.1212	R 1/2	R 1/2	90.5	47.0	21/21

## Shut-off valves with male thread and plug connection

»blue series«

EASY



### Shut-off valve with male thread and plug connection, flow direction from port to tube, parallel male thread with O-ring (NBR)

Art. No.	Type No.	L1 mm	L2 mm	a/f mm
110075	193.018-6	58.0	42.6	14
110076	193.018-8	58.4	42.6	14
110077	193.014-6	59.8	42.6	14
110078	193.014-8	59.9	42.6	17
110079	193.014-10	70.9	47.0	17
110080	193.014-12	70.9	47.0	21
110081	193.038-8	61.4	42.6	17
110082	193.038-10	72.4	47.0	20
110083	193.038-12	71.9	47.0	21
110084	193.012-10	75.9	47.0	24
110085	193.012-12	75.4	47.0	24



### Shut-off valve with male thread and plug connection, flow direction from port to tube, conical male thread, coated

Art. No.	Type No.	L1 mm	L2 mm	a/f mm
110086	192.018-6	58.0	42.6	12
110087	192.018-8	58.9	42.6	14
110088	192.014-6	60.5	42.6	12
110089	192.014-8	60.9	42.6	14
110090	192.014-10	72.4	47.0	17